

Panel Air Conditioner

PAC0500-A111 | Cooling units

Wall-mounted Indoor Panel Air Conditioner

First-of-its-kind, innovative technology setting a new industry benchmark in Panel Air Conditioners.

Features

- Unique Auto Air Filter Cleaning Technology ensures “No more Clogger Air filters”
- Consistent cooling efficiency with best EER - minimises energy costs in demanding environments
- Smart Controller with Modbus TCP & Wi-Fi for remote monitoring and control
- Heavy duty designed for Industrial environment up to 50°C
- CE certified & RoHS compliant, Manufactured in India for Global Market



Technical data

Product properties

Product type	Industrial Panel Air Conditioner
Model number	PAC0500-A111
Fixing type	Wall Mounted
Designed for	Indoor Application
Body material	GI Sheet Steel, SS304 & SS316 options available
Colour	RAL7035 & RAL 5015
Surface treatment	Powder Coated

Performance (DIN EN 14511)

Cooling output L35/L35	505 W
Cooling output L35/L50	400 W
Energy efficiency ratio (EER)	1.68

Electrical data

Rated operating voltage	240 VAC, 1~, 50 Hz
Running current	1.9 A
Rated current (max)	2.2 A
Start-up current	10 A
Power consumption L35/L35	300 W
Power consumption L35/L50	375 W

Airflow

Internal circuit airflow (Unimpeded)	230 m ³ /h
External circuit airflow (Unimpeded)	320 m ³ /h
Internal air direction	Front suction → Front throw
External air direction	Back suction → Top throw

Refrigeration system

Refrigerant	R-134a
Refrigerant quantity	0.310 kg
Global warming potential (GWP)	1430

Noise level

Internal circuit	60 dBA
External circuit	53 dBA

Protection and environmental conditions

Protection – internal circuit	IP54
Protection – external circuit	IP20
Ambient temperature (operation)	10°C ... 50°C
Ambient temperature (storage)	-40°C ... 70°C

Temperature controller

Controller type	Digital Controller / Haima Smart Controller (Smart Model)
Temperature range	+25°C to +45°C
Factory setting	+35°C
Display	LED with touch button / LCD Touch display (Smart Model)
Alarm output	Door Open, Alarm, Temp. Sensors (Smart Model)
Communication	RJ45 Modbus TCP / Wi-Fi (Smart Only)

Construction details

Insulation	Class O Nitrile Butadiene Rubber
Power connection	Plug-in terminal strip
RJ45 connection	RJ45 Female socket

Dimensions and weight

Unit dimensions (W × D × H)	300 × 300 × 700 mm
Box dimensions (W × D × H)	350 × 350 × 800 mm
Net weight	30.5 kg
Gross weight	33 kg

Packaging and logistics

Packing unit	1 piece
Packaging type	Packed in Corrugated Box
Customs tariff number	84158200

Packing unit	1 piece
Packaging type	Packed in Corrugated Box
Customs tariff number	84158200
Country of origin	India

Supply includes

- User Instruction Manual x 1 nos.
- Mounting Bolt & Washer set
- Gasket with Cutout x 1 nos.

Notes

Notes on operation: *The unit must not be operated outside the specified ambient temperature range. Ensure adequate ventilation around the external circuit. Disconnect power before any maintenance or wiring work.*

Refrigerant note: *R-134a is a hydrofluorocarbon (HFC) refrigerant. Handle in accordance with local environmental and safety regulations.*

Environmental product compliance

EU RoHS	CE Compliant – no exemptions
Refrigerant (GWP)	R-134a, GWP 1430
Country of manufacture	India (IN)

Manufactured by:

Pima Controls Pvt Ltd
Ahmedabad, Gujarat, India